


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.18V I:0.1587A P:34.452W PF:0.9434 Freq:49.99Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:4033.9x1 lm		
NAME: LED542 B34 (35W 3000K)	TYPE: 35W	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.: #1
MFR.:	SUR.: 0.155	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 117.09 lm/W			
MODEL	LED542 B34 (35W/3K)	I _{max} (cd)	3372	S/MH(C0/180)	1.00
NOMINAL POWER(W)	35	LOR(%)	100.0	S/MH(C90/270)	1.07
RATED VOLTAGE(V)		TOTAL FLUX(lm)	4033.9	η UP,DN(C0-180)	0.0,47.5
NOMINAL FLUX(lm)	4033.9	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,52.5
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.00
TEST VOLTAGE(V)		η down(%)	100.0	CIBSE SHR MAX	1.10

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-12-09

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
 Humidity:65.0%
 Test Distance:8.690m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C90	C180	C270					γ	Φ zone	Φ total	%lum, lamp
10	3097	3135	3189	3279					0- 10	312.0	312.0	7.73,7.73
20	2597	2676	2697	2887					10- 20	831.3	1143	28.3,28.3
30	2091	2127	2141	2337					20- 30	1125	2268	56.2,56.2
40	980.2	1227	1064	1599					30- 40	1101	3369	83.5,83.5
50	171.2	277.9	204.3	398.0					40- 50	506.0	3875	96.1,96.1
60	37.01	63.77	42.58	87.19					50- 60	115.9	3991	98.9,98.9
70	8.140	18.59	9.889	20.65					60- 70	30.39	4021	99.7,99.7
80	2.439	8.015	3.059	8.410					70- 80	9.753	4031	99.9,99.9
90	0.2379	0.7484	0.3295	0.7180					80- 90	3.109	4034	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 3705.5 lm

%lum = 91.9%

%lamp = 91.9%

Conical surface Flux(120deg): 3990.7 lm

%lum = 98.9%

%lamp = 98.9%

0 - 45 DEG Zonal Flux:3705.5 %lum: 91.9%

0 - 60 DEG Zonal Flux:3990.7 %lum: 98.9%

All measured values may vary less than 35 %

from the average measured value in the 0 to 130 deg. zone: 7.4%

All measured values in the 0 to 130 deg. zone

may vary less than 50% from the average value of itself: 11.3%

C Range: 0 - 360DEG

C Interval: 90.0DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:

Test Date:2021-12-09

γ Range: 0 - 90DEG

γ Interval: 1.0DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446


Humidity:65.0%

Test Distance:8.690m [K=1.0000]

Remarks:

LUMINANCE LIMITATION CURVES

Test:U:230.18V I:0.1587A P:34.452W PF:0.9434 Freq:49.99Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:4033.9x1 lm		
NAME: LED542 B34 (35W 3000K)	TYPE: 35W	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.: #1
MFR.:	SUR.: 0.155	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	68	308
80	90	298
75	120	313
70	153	351
65	251	516
60	477	824
55	873	1418
50	1716	2793
45	3844	5755


C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-12-09

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:8.690m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.18V I:0.1587A P:34.452W PF:0.9434 Freq:49.99Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:4033.9x1 lm		
NAME: LED542 B34 (35W 3000K)	TYPE: 35W	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.: #1
MFR.:	SUR.: 0.155	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.10	1.07	1.05	1.08	1.05	1.03	1.04	1.02	.00	.00	.98	.97	.96	.95	.94	.92
2.0	1.01	.97	.93	.99	.95	.92	.96	.93	.90	.93	.90	.88	.90	.88	.86	.84
3.0	.93	.88	.83	.92	.87	.83	.89	.85	.81	.87	.83	.80	.84	.81	.79	.77
4.0	.86	.80	.75	.85	.79	.75	.83	.78	.74	.81	.76	.73	.79	.75	.72	.70
5.0	.80	.73	.68	.79	.73	.68	.77	.71	.67	.75	.70	.67	.73	.69	.66	.65
6.0	.74	.67	.62	.73	.67	.62	.71	.66	.62	.70	.65	.61	.69	.64	.61	.59
7.0	.69	.62	.57	.68	.62	.57	.67	.61	.57	.65	.60	.57	.64	.60	.56	.55
8.0	.64	.57	.53	.63	.57	.53	.62	.57	.52	.61	.56	.52	.60	.56	.52	.51
9.0	.60	.53	.49	.59	.53	.49	.58	.53	.49	.57	.52	.48	.56	.52	.48	.47
10.0	.56	.50	.45	.56	.50	.45	.55	.49	.45	.54	.49	.45	.53	.48	.45	.44



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-12-09

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:8.690m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:230.18V I:0.1587A P:34.452W PF:0.9434 Freq:49.99Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:4033.9x1 lm		
NAME: LED542 B34 (35W 3000K)	TYPE: 35W	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.: #1
MFR.:	SUR.: 0.155	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.195	.111	.035	.189	.108	.034	.176	.101	.032	.164	.095	.030	.153	.089	.029		
2.0	.189	.104	.032	.184	.101	.031	.173	.096	.030	.163	.091	.029	.154	.087	.027		
3.0	.181	.097	.029	.176	.094	.028	.167	.091	.028	.159	.087	.027	.151	.083	.026		
4.0	.173	.090	.026	.169	.088	.026	.161	.085	.025	.153	.082	.025	.146	.080	.024		
5.0	.165	.084	.024	.161	.083	.024	.154	.080	.024	.148	.078	.023	.142	.076	.023		
6.0	.158	.079	.023	.154	.078	.022	.148	.076	.022	.142	.074	.022	.137	.072	.021		
7.0	.150	.074	.021	.147	.073	.021	.142	.072	.021	.137	.070	.020	.132	.068	.020		
8.0	.144	.070	.020	.141	.069	.020	.136	.068	.019	.131	.067	.019	.127	.065	.019		
9.0	.137	.066	.019	.135	.066	.018	.130	.065	.018	.126	.063	.018	.122	.062	.018		
10.0	.131	.063	.017	.129	.062	.017	.125	.061	.017	.121	.060	.017	.118	.059	.017		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.172	.157	.143	.147	.135	.123	.101	.093	.085	.058	.054	.050	.019	.017	.016	
2.0	.159	.132	.110	.136	.114	.095	.093	.079	.067	.054	.046	.039	.017	.015	.013	
3.0	.147	.114	.087	.126	.098	.075	.087	.068	.053	.050	.040	.031	.016	.013	.010	
4.0	.138	.099	.070	.119	.086	.060	.082	.060	.043	.047	.035	.025	.015	.011	.008	
5.0	.130	.088	.057	.112	.076	.049	.077	.053	.035	.045	.031	.021	.014	.010	.007	
6.0	.123	.079	.047	.106	.068	.041	.073	.048	.029	.042	.028	.017	.014	.009	.006	
7.0	.117	.072	.040	.101	.062	.035	.070	.044	.025	.040	.026	.015	.013	.008	.005	
8.0	.112	.066	.034	.096	.057	.030	.066	.040	.021	.039	.024	.013	.013	.008	.004	
9.0	.107	.061	.030	.092	.053	.026	.064	.037	.018	.037	.022	.011	.012	.007	.004	
10.0	.102	.056	.026	.088	.049	.023	.061	.034	.016	.036	.020	.010	.012	.007	.003	

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-12-09

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:8.690m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.18V I:0.1587A P:34.452W PF:0.9434 Freq:49.99Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:4033.9x1 lm		
NAME: LED542 B34 (35W 3000K)	TYPE: 35W	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.: #1
MFR.:	SUR.: 0.155	Shielding Angle:

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	14.0	15.1	14.2	15.2	15.4	14.7	15.7	14.9	15.9	16.1
3H	13.8	14.8	14.1	15.0	15.2	14.5	15.5	14.8	15.7	15.9
4H	13.7	14.7	14.0	14.9	15.1	14.4	15.4	14.7	15.6	15.8
6H	13.6	14.5	13.9	14.8	15.0	14.4	15.2	14.7	15.5	15.7
8H	13.6	14.4	13.9	14.7	15.0	14.3	15.1	14.6	15.4	15.7
12H	13.5	14.3	13.9	14.6	14.9	14.3	15.1	14.6	15.3	15.6
4H 2H	13.7	14.7	14.0	14.9	15.1	14.4	15.4	14.7	15.6	15.8
3H	13.6	14.4	13.9	14.7	14.9	14.3	15.1	14.6	15.3	15.6
4H	13.5	14.2	13.8	14.5	14.8	14.2	14.9	14.6	15.2	15.5
6H	13.4	14.0	13.8	14.4	14.7	14.1	14.8	14.5	15.1	15.4
8H	13.4	13.9	13.8	14.3	14.7	14.1	14.7	14.5	15.0	15.4
12H	13.3	13.8	13.7	14.2	14.6	14.0	14.6	14.5	15.0	15.3
8H 4H	13.4	13.9	13.8	14.3	14.7	14.1	14.6	14.5	15.0	15.4
6H	13.3	13.7	13.7	14.1	14.6	14.0	14.5	14.4	14.9	15.3
8H	13.2	13.6	13.7	14.1	14.5	14.0	14.4	14.4	14.8	15.2
12H	13.2	13.5	13.6	14.0	14.4	13.9	14.3	14.4	14.7	15.2
12H 4H	13.3	13.8	13.7	14.2	14.6	14.0	14.5	14.4	14.9	15.3
6H	13.2	13.6	13.7	14.1	14.5	13.9	14.4	14.4	14.8	15.2
8H	13.2	13.5	13.6	14.0	14.4	13.9	14.3	14.4	14.7	15.2
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 2.5 / -10.5					+ 2.8 / - 8.5				
1.5H	+ 4.5 / - 7.6					+ 4.5 / - 7.4				
2.0H	+ 5.7 / - 6.8					+ 6.3 / - 6.9				

CIE Pub.117, 4034 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 4.8$)
Area: 0.155 m²

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-12-09

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:8.690m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:230.18V I:0.1587A P:34.452W PF:0.9434 Freq:49.99Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:4033.9x1 lm		
NAME: LED542 B34 (35W 3000K)	TYPE: 35W	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.: #1
MFR.:	SUR.: 0.155	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	81	74	69	80	73	69	80	73	69	65
0.80	90	83	78	89	82	78	88	82	78	73
1.00	95	89	85	94	88	84	93	88	84	79
1.25	100	94	90	99	94	90	97	92	89	84
1.50	103	98	94	102	97	94	100	96	92	88
2.00	107	102	99	105	101	98	103	99	96	91
2.50	109	104	101	107	103	100	104	101	98	92
3.00	111	107	104	109	105	103	105	103	100	94
4.00	113	110	107	111	108	106	107	105	103	96
5.00	114	111	109	112	110	108	108	106	105	97
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-12-09

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:8.690m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:230.18V I:0.1587A P:34.452W PF:0.9434 Freq:49.99Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:4033.9x1 lm		
NAME: LED542 B34 (35W 3000K)	TYPE: 35W	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.: #1
MFR.:	SUR.: 0.155	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-12-09

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:8.690m [K=1.0000]
Remarks:

AAI Figure

Test:U:230.18V I:0.1587A P:34.452W PF:0.9434 Freq:49.99Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:4033.9x1 lm		
NAME: LED542 B34 (35W 3000K)	TYPE: 35W	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.: #1
MFR.:	SUR.: 0.155	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-12-09

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:8.690m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:230.18V I:0.1587A P:34.452W PF:0.9434 Freq:49.99Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:4033.9x1 lm		
NAME: LED542 B34 (35W 3000K)	TYPE: 35W	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.: #1
MFR.:	SUR.: 0.155	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2021-12-09

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity: 65.0%
Test Distance: 8.690m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:230.18V I:0.1587A P:34.452W PF:0.9434 Freq:49.99Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:4033.9x1 lm		
NAME: LED542 B34 (35W 3000K)	TYPE: 35W	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.: #1
MFR.:	SUR.: 0.155	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	282
L_0~180(75)av	132
L_0~180(85)av	80
L_90~270(65)av	582
L_90~270(75)av	318
L_90~270(85)av	321
L_45(65)av	472
L_45(75)av	249
L_45(85)av	232

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-12-09

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:8.690m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2021-12-09

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity: 65.0%
Test Distance: 8.690m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:8.690m [K=1.0000]
Remarks:

```