




SPECIFICATIONS

DIMENSIONS	D421 x H385mm
COLOUR TEMP	3000K, 4000K or 5000K
CRI	90
LIFESPAN	<60,000 hours (L80 B10)
BEAM ANGLE	90° (Low-glare)
MATERIAL	Aluminium / Polycarbonate
IP RATING	IP65
DRIVER	Incorporated, (non-dimmable). Pre-wired with three pin plug, 1.5m cable length. DALI and 1-10V available on indent order MOQs apply.
APPLICATION	Supermarkets, shopping malls, retail showrooms
INRUSH	65.5A @ 912µs (P475 180W)
DRIVERS PER MCB	B16=7 / C16=11 (P475 180W)
AMBIENT TEMP	-30.. +50° C
WEIGHT	4.8-5kg
WARRANTY	5 Year Warranty

ACCESSORIES

DESCRIPTION	CODE
Bottom Cap (PC)	P470 PCBC
250mm Chain with Snap Links	P700-CH250
500mm Chain with Snap Links	P700-CH500
1000mm Chain with Snap Links	P700-CH1000



<21,200
LUMENS

<180
WATTS

AC
240V

AVAILABLE IN

DESCRIPTION	CODE
50W, 3000K, 6085lm	P471 3KR
50W, 4000K, 6085lm	P471 4KR
100W, 4000K, 12055lm	P472 4KR
150W, 4000K, 17790lm	P474 4KR
180W, 4000K, 21200lm	P475 4KR

INDENT OPTIONS

MOQ applies.

DESCRIPTION	CODE
50W, 5000K, 6085lm	P471 5KR
100W, 3000K, 12055lm	P472 3KR
100W, 5000K, 12055lm	P472 5KR
120W, 3000K, 14530lm	P473 3KR
120W, 4000K, 14530lm	P473 4KR
120W, 5000K, 14530lm	P473 5KR
150W, 3000K, 17790lm	P474 3KR
150W, 5000K, 17790lm	P474 5KR
180W, 3000K, 21200lm	P475 3KR
180W, 5000K, 21200lm	P475 5KR