



SPECIFICATIONS

DIMENSIONS	D340 x H110mm
COLOUR TEMP	4000K Natural White or 5700K Daylight
LUMENS	77W / 14,000lm 96W / 17,000lm 111W / 19,500lm 132W / 23,000lm 150W / 25,500lm (default factory setting)
CRI	80
LIFESPAN	57,000 hours (L80 B10)
BEAM ANGLE	90°
MATERIAL	Aluminium / PC
IP RATING	IP65
IK RATING	IK08
DRIVER	Incorporated, modular quick release plug and play driver pre-wired with 1500mm lead and three pin plug.
TLAs	"Flicker-free", Pst≤1.0; SVM ≤0.4 at Full Load to avoid stroboscopic effect in rotating machinery
DIMMING	Individually Dimmable to 10% (in 5% intervals) via remote control when installed with plug and play sensor accessory
SENSOR	Motion and Daylight sensor accessory available. Remote adjustable power output, detection area, hold time, daylight threshold, stand-by period and stand-by dimming level. Default sensor factory settings: Detection area: 100%, Hold time: 3min, Daylight threshold: 200 lux, Stand-by period: 10s, Stand-by dimming level: 50%.
APPLICATION	Industrial Highbay
POWER FACTOR	>0.90
INRUSH	50A @ 400µs
DRIVERS PER MCB	B16=5 / C16=9
AMBIENT TEMP	-30°C to +50°C
WEIGHT	2600g
WARRANTY	5 Year Warranty

<25,500 LUMENS	<150 WATTS	AC 240V
--------------------------	----------------------	----------------

AVAILABLE IN

DESCRIPTION	CODE
4000K, Selectable Output Driver	P700 4KA
4000K, Selectable Output Driver. 4 Pack.	P700 4KA4P
4000K, DALI	P700 4KDD
5700K, Selectable Output Driver	P700 57KA
5700K, DALI	P700 57KDD

ACCESSORIES

DESCRIPTION	CODE
Sensor	P700 S1
Remote Control for Sensor, Digital Display	P700 R1
Glare Shield	P700 GS1
Surface Mount Bracket	P700 SMB
250mm Chain with Snap Links	P700-CH250
500mm Chain with Snap Links	P700-CH500
1000mm Chain with Snap Links	P700-CH1000
Casambi control module	P700 CAS1